


Standard Counterbalance 3:1

標準 抗衡閥 3:1



Model Code 產品型號	Cavity 閥孔型號	Capacity 流量 (l/min)	Dimension 尺寸 (mm)			Torque 安裝扭力 (Nm)	Weight 重量 (kg)	Max. Pressure 最大壓力 (bar)
			a	b	c			
CB2A	T11A	60	34.9	22.2	50	40/50	0.17	350
CB3A	T2A	120	34.9	28.6	61	60/70	0.30	350
CB6A	T17A	240	46.0	31.8	70	200/215	0.64	350
CB8A	T19A	480	63.5	41.3	90	465/500	1.47	350


Turn screw clockwise to reduce setting and release load
順時針方向旋轉：降壓

逆時針方向旋轉：增壓

Full Adjustment

3 turns

全調三圈



Option Ordering Information

選購型號

CB 2 A - T11A - L I N

① Model Code 產品型號

② Capacity (l/min) 流量

2: 60 3: 120 6: 240 8: 480

③ Pilot Ratio 導壓比

A: 3:1

④ Cavity 閥孔型號

T11A T2A T17A T19A

⑤ Control 控制方式

L: standard screw adjustment 標準螺絲調整

⑥ Functional Setting Range 設定範圍

Code 編號	H	I	A	B
Adjustment range (bar) 調壓範圍	70~280	28~105	70~280	28~105
Check (bar) 止回彈簧壓力	1.7	1.7	0.3	0.3
Standard setting (bar) 出廠設定壓力	210	70	210	70

⑦ Seal 油封材質

N: buna-N V: viton

Performance Curves

性能曲線

Free Flow & Piloted Open

Pressure Drop

自由流及導壓開壓降曲線

