


Ventable, Pilot Operated Relief with Drain to Port 4

透氣口控制 四口排油 平衡式溢流閥



Model Code 產品型號	Cavity 閥孔型號	Capacity 流量 (l/min)	Dimension 尺寸 (mm)				Torque 安裝扭力 (Nm)	Weight 重量 (kg)	Max. Pressure 最大壓力 (bar)
			a	b	c				
					L	K			
RV2D	T21A	60	35.1	22.2	78.5	84.8	45/50	0.20	350
RV3D	T22A	120	35.1	28.6	87.4	93.7	60/70	0.35	350
RV6D	T23A	240	46.0	31.8	99.8	106.4	200/215	0.75	350
RV8D	T24A	480	63.5	41.3	121.4	127.8	465/500	1.75	350

Option Ordering Information

選購型號

RV 2 D - T21A - L A N

① Model Code 產品型號

② Capacity (l/min) 流量

2: 60 3: 120 6: 240 8: 480

③ Cavity 閥孔型號

T21A T22A T23A T24A

④ Control 控制方式

L: standard screw adjustment 標準螺絲調整


K: handknob with lock knob 調鈕調整

⑤ Adjustment Range (bar) 調壓範圍

A: 7~210 B: 3.5~105 C: 10.5~420 N: 5~55

⑥ Seal 油封材質

N: buna-N V: viton



Performance Curves

性能曲線

Vented Pressure Drop

透氣壓降曲線

